



Carrydeck[®] Industrial Cranes



**5500 Series
15 Ton Capacity**



**3300 Series
9 Ton Capacity**

The Carrydeck line of industrial cranes from Shuttlelift, Inc. offers you a durable, versatile and productive crane in a compact design. Featuring complete mobility with a telescoping boom and a convenient load deck, Carrydeck industrial cranes have a profile advantageous for indoor and outdoor use.



**7700 Series
20 Ton Capacity**

Carrydeck Cranes

	3330 ELB	3340	5540	5550RT	5560RT	7750RT
Max. Capacity: 5' Radius on Outriggers, 360°	17,000 lb (7711 kg)	18,000 lb (8165 kg)	-	-	-	-
6' Radius, on Outriggers, 360°	-	-	30,000 lb (13 608 kg)	30,000 lb (13 608 kg)	30,000 lb (13 608 kg)	-
10' Radius, on Outriggers, 360°						40,000 lb (18 144 kg)
Unit Weight	17,280 lb (7845 kg)	16,600 lb (7536 kg)	26,500 lb (12 020 kg)	29,000 lb (13 166 kg)	30,700 lb (13 938 kg)	43,000 lb (19 522 kg)
Deck Carrying Capacity	14,000 lb (6350 kg)	14,000 lb (6350 kg)	20,000 lb (9072 kg)	20,000 lb (9072 kg)	20,000 lb (9072 kg)	30,000 lb (13 608 kg)
Max. Main Boom Length (horizontal boom pin to center of block)						
3-Section Boom	30' 2" (9.19 m)	32' 10" (10.01 m)	40' 0" (12.19 m)	-	-	-
4-Section Boom	39' 8" (12.09 m)	-	-	43' 6" (13.26 m)	54' 6" (16.61 m)	-
5-Section Boom	-	-	-	-	-	67' 0" (20.42 m)
Jib/Boom Extension Length	10' (3.05 m)	12' (3.66 m) 18' (5.49 m)	15' (4.57 m)	15' (4.57 m)	15' (4.57 m)	17' (5.18 m)
Max. Main Boom Hook Height	37' 6" (11.4 m)	34' 6" (10.52 m)	43' 10" (13.36 m)	48' 1" (14.66 m)	58' (17.68 m)	73' (22.25 m)
Max. Hook Height w/swing around jib	46' (14.02 m)	52' (15.85 m)	58' 10" (17.93 m)	63' 1" (19.23 m)	73' (22.25 m)	90' (27.43 m)
Standard Engine: Cummins Diesel 4b3.9 - 4 cylinder	75 HP	80 HP	80 HP	110 HP Turbo	110 HP Turbo	130 HP Turbo After-Cooled
Optional Engine: Continental 2.7L Gas	68 HP	-	-	-	-	-
GM 3.0L (EFI) Dual Fuel	-	70 HP	-	-	-	-
GM 4.3L Dual Fuel	-	-	100 HP	100 HP	100 HP	N.A.
Steering Wheels	2 or 4	2 or 4	2 or 4	2 or 4	2 or 4	2 or 4
Drive Axle	Front	Front	Front-Standard & Rear-Optional	Front & Rear	Front & Rear	Front & Rear
Turning Radius (CL to outside of wheel) 4-Wheel Steer	10' 2" (3.10 m)	9' 4.75" (2.86 m)	12' 4" (3.76 m)	12' 4" (3.76 m)	12' 4" (3.76 m)	12' 11" (3.94 m)
Wire Rope	7/16" EIPS IWRC 6X19	9/16" EEIPS IWRC 6X19	1/2" EIPS IWRC 6X19	1/2" EIPS IWRC 6X19	1/2" EIPS IWRC 6X19	9/16" EEIPS IWRC 6X19
Tire Size	10.00 x 15 14PR	10.00 x 15 14PR	385/65R22.5 Radial	385/65R22.5 Radial	385/65R22.5 Radial	14.00R24 Radial
Dimensions: Overall Length - Transport Position	16' 3" (4.95 m)	18' 0" (5.49 m)	21' 6" (6.55 m)	19' 8" (5.99 m)	22' 8" (6.91 m)	24' 9" (7.54 m)
Overall Height - Transport Position	7' 10" (2.21 m)	7' 3" (2.41 m)	7' 11" (2.41 m)	7' 11" (2.41 m)	7' 11" (3.00 m)	9' 10" (4.67 m)
Overall Width - Outrigger Extended	11' 8" (3.56 m)	11' 2" (3.40 m)	13' 10" (4.22 m)	13' 10" (4.22 m)	13' 10" (4.22 m)	15' 4" (4.67 m)
Overall Width - Outrigger Retracted	6' 7" (2.01 m)	6' 7" (2.01 m)	7' 9.5" (2.37 m)	7' 9.5" (2.37 m)	7' 9.5" (2.37 m)	8' 0" (2.44 m)

Authorized Representative



SHUTTLELIFT, INC., 49 E. Yew St., P.O. Box 66,
Sturgeon Bay, WI 54235 USA

Ph: 920-743-8650 • FAX: 920-743-1522 • E-mail: sales@shuttlelift.com

www.shuttlelift.com